

Correas trapeciales de flancos abiertos y troqueladas

Perfil 5VX (15x13mm.)

(RMA/MPTA IP 22)

Referencia	La
5VX 450	1150
5VX 470	1190
5VX 490	1250
5VX 500	1270
5VX 510	1290
5VX 530	1345
5VX 540	1370
5VX 550	1400
5VX 560	1420
5VX 570	1450
5VX 580	1470
5VX 590	1500
5VX 600	1525
5VX 610	1550
5VX 630	1600
5VX 650	1650
5VX 660	1680
5VX 670	1700
5VX 680	1730
5VX 690	1750
5VX 710	1800
5VX 730	1850
5VX 740	1880
5VX 750	1900
5VX 780	1980
5VX 800	2030
5VX 810	2060
5VX 830	2110
5VX 840	2130
5VX 850	2160
5VX 860	2180

www.indarbelt.es

Referencia	La
5VX 880	2240
5VX 900	2290
5VX 930	2360
5VX 950	2410
5VX 960	2440
5VX 1000	2540
5VX 1030	2620
5VX 1060	2690
5VX 1080	2740
5VX 1120	2840
5VX 1150	2920
5VX 1160	2950
5VX 1180	3000
5VX 1230	3130
5VX 1250	3180
5VX 1320	3350
5VX 1400	3550
5VX 1500	3810
5VX 1600	4060
5VX 1700	4320
5VX 1800	4570
5VX 1900	4830
5VX 2000	5080



Li = Desarrollo interior en mm.
Lp(Lw)= Desarrollo primitivo en mm.
La = Desarrollo exterior en mm.



C/ Dres. Carmelo y Gil 12. 48012 Bilbao. Spain.
Tfno:+34 94 470 18 62 Fax:+34 94 470 08 61

<http://www.indarbelt.es>

e-mail: indarbelt@indarbelt.es