

Correas trapeciales perfil 32/D (32x19mm.)

(DIN 2215)

Referencia	Li mm.	Lp mm.
D 98	2500	2576
D 104	2650	2726
D 110	2800	2876
D 118	3000	3076
D 120	3048	3124
D 124	3150	3226
D 128	3251	3327
D 136	3454	3530
D 137	3475	3551
D 140	3550	3626
D 144	3658	3734
D 154	3914	3990
D 158	4013	4089
D 162	4115	4191
D 170	4310	4386
D 173	4394	4470
D 177	4500	4576
D 180	4572	4648
D 187	4750	4826
D 195	4953	5029
D 197	5000	5076
D 204	5182	5258
D 205	5209	5285
D 207	5259	5335
D 210	5334	5410
D 223	5600	5676
D 225	5659	5735
D 236	5940	6016
D 238	6000	6076
D 240	6039	6115
D 248	6244	6320
D 250	6294	6370
D 255	6424	6500
D 266	6700	6776
D 270	6804	6880
D 282	7100	7176
D 285	7184	7260
D 298	7500	7576
D 300	7565	7641

www.indarbelt.es



Li = Desarrollo interior en mm.
Lp(Lw)= Desarrollo primitivo en mm.
La = Desarrollo exterior en mm.



C/ Dres. Carmelo y Gil 12. 48012 Bilbao. Spain.
Tfno:+34 94 470 18 62 Fax:+34 94 470 08 61

<http://www.indarbelt.es>

e-mail: indarbelt@indarbelt.es