

Correas trapeciales perfil 10/Z (10x6mm.)

(DIN 2215)

Referencia	Li mm.	Lp mm.
Z 16	410	435
Z 17¼	440	465
Z 18	460	485
Z 19	480	505
Z 19½	500	525
Z 20½	520	545
Z 21	530	555
Z 21¼	540	565
Z 21½	545	570
Z 21¾	555	580
Z 22	560	585
Z 22¼	565	590
Z 22½	575	600
Z 23	585	610
Z 23½	600	625
Z 23¾	605	630
Z 24	610	635
Z 24¾	630	655
Z 25	635	660
Z 25½	650	675
Z 26	660	685
Z 26½	670	695
Z 27	685	710
Z 27½	700	725
Z 28	710	735
Z 28½	725	750
Z 29	735	760
Z 29½	750	775
Z 30	765	790
Z 30½	775	800
Z 30¾	785	810
Z 31½	800	825
Z 32	815	840
Z 32½	825	850
Z 33	840	865
Z 33½	850	875
Z 34	865	890
Z 34¼	870	895
Z 34½	875	900
Z 35	890	915
Z 35½	900	925
Z 36	915	940
Z 36½	925	950
Z 36¾	935	960
Z 37	945	970
Z 37½	950	975
Z 38	965	990
Z 38¼	975	1000
Z 39	1000	1025
Z 40	1016	1041
Z 40½	1030	1055
Z 41	1040	1065
Z 41½	1050	1075
Z 41¾	1060	1085
Z 42	1070	1095
Z 42½	1080	1105
Z 43	1090	1115
Z 43¼	1100	1120
Z 44	1120	1145

www.indarbelt.es

Referencia	Li mm.	Lp mm.
Z 45	1145	1170
Z 46	1180	1205
Z 47	1194	1219
Z 47¾	1215	1240
Z 48	1225	1250
Z 49	1245	1270
Z 50	1270	1295
Z 50½	1285	1310
Z 51	1300	1325
Z 52	1320	1345
Z 53	1345	1370
Z 54	1371	1396
Z 55	1400	1425
Z 56	1422	1447
Z 57	1450	1475
Z 59	1500	1525
Z 59½	1515	1540
Z 61	1550	1575
Z 62	1575	1600
Z 63	1600	1625
Z 65	1651	1676
Z 66	1675	1700
Z 67	1700	1725
Z 68½	1740	1765
Z 69	1750	1775
Z 71	1803	1828



Li = Desarrollo interior en mm.
 Lp(Lw)= Desarrollo primitivo en mm.
 La = Desarrollo exterior en mm.



C/ Dres. Carmelo y Gil 12. 48012 Bilbao. Spain.
 Tfno:+34 94 470 18 62 Fax:+34 94 470 08 61

<http://www.indarbelt.es>

e-mail: indarbelt@indarbelt.es