

Tsubaki

Antirretornos de Levas. Serie PB

Modelo	Max Par (N-m)	Arrastre de Sobregiro (N-m)	Max Sobregiro (r/min)		Max Indexación (ciclos/min.)	Tamaño del Eje		A	B	C (h7)	D	E	F	G	Pista Exterior Chavetero		Peso (kg)	Lubricación (Tamaño x Paso)
			Pista Interior	Pista Exterior		Día (J7)	Chavetero								K	L		
PB 3	29,4	0,196	1800	900	150	10	4x1,5	50	50	23	22	25	21	25,7	4x2,5	16	0,23	M6xP1,0
PB 5	147	0,196	1800	900	150	16	5x2,0	70	60	32	32	35	25	38,8	5x3,0	20	0,58	M6xP1,0
PB 6	382	0,196	1500	800	150	20	5x2,0	82	73	38	38	37	33	41,0	5x3,0	27	1,1	M6xP1,0
PB 8	568	0,294	1200	650	150	25	7x3,0	85	83	45	40	45	33	42,0	7x4,0	27	1,6	M6xP1,0
PB 10	843	0,392	1000	400	150	31,5	10x3,5	92	95	60	41	60	37	44,0	10x4,5	28	2,5	M6xP1,0
PB 12	1530	0,392	800	300	150	40	10x3,5	100	113	65	50	66	37	52,6	10x4,5	29	3,6	M6xP1,0
PB 14	2110	0,588	700	300	150	45	12x3,5	112	133	75	54	76	41	57,3	12x4,5	30	6,0	M6xP1,0

